



DET NORSKE VERITAS

EC TYPE-EXAMINATION CERTIFICATE

Application of: Council Directive 96/98/EC of 20 December 1996 on Marine Equipment as amended by directive 2009/26/EC, issued as "Forskrift om Skipsutstyr" by the Norwegian Maritime Directorate. This Certificate is issued by Det Norske Veritas under the authority of the Government of the Kingdom of Norway.

CERTIFICATE NO. **MED-B-6382**

This is to certify that the
Surface materials and floor coverings with low flame-spread characteristics: floor coverings

with type designation(s)
SikaFloor® 264


Manufacturer
Sika Services AG
ZURICH, Switzerland

is found to comply with the requirements in the following Regulations/Standards:
Annex A.1, item No. A.1/3.18c and Annex B, Module B in the Directive. SOLAS 74, Reg. II-2/3, II-2/5, II-2/6, II-2/9 & X/3, IMO MSC/Circ. 1120, 2000 HSC Code 7 and IMO FTP Code

Further details of the equipment and conditions for certification are given overleaf.

Høvik, 2010-11-10
for **Det Norske Veritas AS**

This Certificate is valid until
2015-11-10



Notified Body No.: **0575**

Eivind Mykland
Head of Department

DNV local office:
Essen

Rolf Emilsen
Surveyor



The Certificate is subject to terms and conditions overleaf. Any significant changes in design or construction of the product, or amendments to the Directive or Standards referenced above may render this Certificate invalid. The product liability rests with the manufacturer or his representative in accordance with Council Directive 96/98/EC, as amended. The Mark of Conformity may only be affixed to the product and a Declaration of Conformity may only be issued when the production/product assessment module referred to in the council directive, is fully complied with.



Certificate No.: MED-B-6382
Item No.: A1/3.18c
Job Id.: 344.1-002759-1

Product description

"SikaFloor® 264"

2-component epoxy resin, mixed with quarzsand (mixing ratio 1:0,7). Thickness 2-3 mm. Density 1,5 kg/l. Broadcasting with quarzsand, thickness 0,4-0,7 mm. Top coated with SikaFloor® 169 2- component epoxy topcoat 200 g/m².
Max thickness: 4 mm.

Applications/Limitations

Low flame spread surface material, not generating excessive quantities of smoke nor toxic products in fire.
Approved for use as floor covering on non-combustible substrate throughout the accommodation.

Each product is to be supplied with its manual for application and maintenance.

Type Examination documentation

Test reports: No. PX00021B dated 23 February 2010 and No. PX00021D dated 12 May 2010 from SP, Borås, Sweden.

Tested according to IMO FTPC Parts 2 and 5.

Marking of product

The product or packing is to be marked with name of manufacturer, type designation, MED Mark of Conformity and USCG approval if applicable (see below).

Mark of Conformity

The manufacturer is allowed to affix the Mark of Conformity according to Article 11 in the Council Directive 96/98/EC on Marine Equipment and shall issue a Declaration of Conformity, only when the module D or E or F of Annex B in the same directive is fully complied with.

Module D: The quality system for production and testing shall be approved by the Notified Body.

Module E: The quality system for inspection and testing shall be approved by the Notified Body.

Module F: Compliance of the products to type as described in this EC Type-Examination Certificate must be verified by the Notified Body who also shall issue a of Certificate Conformity.

USCG Approval

An U.S. Coast Guard approval number will be assigned to the equipment when the production module has been completed and will appear on the production module certificate (module D, E or F), as allowed by the "Agreement between the United States of America and the EEA EFTA states on the mutual recognition of certificates of conformity for marine equipment" signed 17 October 2005.

